

SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION	
Product identifier used on the label:	
Product Name:	Westco HRA Resins
SDS Manufacturer Number:	62
Other means of identification:	
Product Description:	C9 Aromatic Hydrocarbon Resin; Pale yellow granule/flake
Synonyms:	Westco HRA 70, Westco HRA 95, C9 Aromatic Hydrocarbon Resin
Recommended use of the chemical and re	strictions on use
Product Use/Restriction:	HRA resins can be used in rubber compounds as a plasticizer, softener, tackifier and/or processing aid. In heavily loaded stocks they act as a dispersion aid.
Chemical distributor, or other responsible r	party Name, address, and telephone number:
Distributor Name:	Western Reserve Chemical Corporation
Address:	4837 Darrow Road Stow, OH 44224 USA
General Phone Number:	330 650 2244
General Fax Number:	330 650 2255
Emergency phone number::	
Emergency Phone Number:	Chemtrec 1 800 424 9300 USA
Website:	www.wrchem.com

SECTION 2 : HAZARD(S) IDENTIFICATION

 $\underline{Classification \ of \ the \ chemical \ in \ accordance \ with \ CFR \ 1910.1200(d)(f):}$

GHS Pictograms:	
Signal Word:	Warning
GHS Class:	Classification of the substance or mixture Classification (GHS-US) Combustible Dust Carcinogenicity Category 2
Hazard Statements:	*May form combustible dust concentrations in air. * Suspected of causing cancer.
Precautionary Statements:	 * Obtain special instructions before use. * Do not handle until all safety precautions have been read and understood. * Wear protective gloves/protective clothing/eye protection/face protection. * IF exposed or concerned: Get medical advice/attention. * Store locked up. * Dispose of contents/container in accordance with Local, State, Federal and International regulations.

 $\underline{\textit{Hazards not otherwise classified that have been identified during the classification process:}$

Aromatic Hydrocarbon Resin

Route of Exposure:	Eyes. Skin. Inhalation. Ingestion.	
Eye:	Dusts from this product may cause eye irritation.	
Skin:	Repeated or prolonged contact may cause slight irritation to the skin.	
Inhalation:	Dusts from this product may cause respiratory irritation. Vapors formed when material is processed at high temperatures may be irritating to the upper respiratory tract.	
Carcinogenicity:	Suspected of causing cancer.	
Potential Environmental Effects:	Harmful to aquatic life with long lasting effects.	
Signs/Symptoms:	Potential Adverse human health effects and symptoms : Dust or particulates may cause mild respiratory tract and eye irritation. Product may cause mild skin irritation.	
Notes :	Contact with skin or eyes with hot material may cause serious thermal burns	

Westco HRA Resins

Revision:: 7/18/16

to skin or eyes.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixtures:</u> Chemical Name	CA S#	Ingredient Percent	EC Num.
Aromatic Hydrocarbon Resin	68410-16-2	≥ 99 %	
Naphthalene	91-20-3	< 1 %	

Description of necessary m	easures:
Eye Contact:	First-aid measures after eye contact : Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking, tears or redness persist.
Skin Contact:	First-aid measures after skin contact : Wash with plenty of soap and water. If irritation persists, consult a doctor. Heated Material: For serious burns from heated material, get medical attention. In case of skin contact, immediately immerse in or flush with clean, cold water. Do not attempt to remove adhered material from skin.
Inhalation:	First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing.
Ingestion:	First-aid measures after ingestion : Do NOT induce vomiting unless directed to do so by medical personnel.
Notes :	Most important symptoms and effects, both acute and delayed Symptoms/injuries:Chronic (long-term) health effects may result from repeated overexposure.
	Indication of any immediate medical attention and special treatment needed : Treat symptomatically.

SECTION 5 : FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:		
Suitable Extinguishing Media:	Carbon dioxide. Foam. Dry chemical. Water spray or fog.	
Unusual Fire Hazards:	Fire hazard : May form combustible dust concentrations in overheating/melting/decomposition may be flammable an	

Fire hazard : May form combustible dust concentrations in air. Vapors generated from overheating/melting/decomposition may be flammable and may cause fire/explosion if source of ignition is present. Explosion hazard : Potential dust explosion hazard. When dust becomes airborne and is exposed to an ignition source, sufficient combustible/flammable dust may exist to burn in the open or explode if confined.

Special protective equipment and precautions for fire-fighters:		
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.	
Fire Fighting Instructions:	Use water spray or fog for cooling exposed containers. Avoid raising powdered materials into airborne dust, creating an explosion hazard. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion. Exercise caution when fighting any chemical fire. Prevent firefighting water from entering environment. Fight fire from safe distance and protected location.	
Notes :	Hazardous decomposition products in case of fire : Carbon oxides (CO, CO2). Toxic fumes.	

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:		
Personal Precautions:	Emergency procedures for non-emergency personnel : Remove ignition sources. Ensure adequate ventilation. Evacuate unnecessary personnel. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
	Emergency procedures for emergency responders : No additional requirement.	
Environmental precautions:		
Environmental Precautions:	Avoid release to the environment.	
Methods and materials for contain	ment and cleaning up:	
Methods for containment:	Sweep up or vacuum up the product. Avoid creating or spreading dust. Spilled material may present a slipping hazard.	
Methods for cleanup:	Dispose of solid materials or residues at a licensed site.	
Notes :	Reference to other sections : See section 8. Exposure controls and personal protection.	

Precautions for safe handling:

Handling:	Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with elevated temperature or molten product to prevent burns. Avoid raising powdered material due to explosion hazard. Prevent the build-up of electrostatic charge. Use only non-sparking tools. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. The plastic packaging film used to secure bags of material on pallets can also develop static electricity remove packaging film in an area free from ignitable vapors/dust. Refer to the latest edition of the National Fire Protection Association (NFPA) 654 publication, Standard for the Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries, for complete discussion on dust explosion prevention and control measures. This material may be shipped as a viscous, molten product at elevated temperatures (approximately 177 °C), but below its flashpoint, to facilitate transfer to storage containers or processing vessels.	
Hygiene Practices:	Do not eat, drink or smoke when using this product. Always wash hands after handling the product	
Conditions for safe storage, including any incompatibilities:		
Storage:	Technical measures : Electrical equipment should conform to the National Electric Code. The plastic packaging film used to secure bags of material on pallets can also develop static electricity remove packaging film in an area free from ignitable vapors/dust. Protect from freezing. If frozen, thaw and mix thoroughly before use. Storage conditions : Keep container tightly closed. Store in a dry place. Flaked forms may degrade by gradual oxidation. Maximum storage period : 12 months Storage temperature : < 40 °C	
Specific end use(s):		
Work Practices:	Safety showers and eye wash stations should be available.	
Notes :	Incompatible products : Oxidizing agents.	

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:		
Aromatic Hydrocarbon Resin :		
Guideline ACGIH:	ACGIH TWA (mg/m³): 10 mg/m³ (inhalable dust) 3 mg/m³ (respirable dust) USA ACGIH Remark (ACGIH) Particulates, not otherwise classified.	
Guideline OSHA:	USA OSHA OSHA PEL (TWA) (mg/m³) 15 mg/m³ (total dust) 5 mg/m³ (respirable dust) USA OSHA Remark (US OSHA) Particulates, not otherwise classified	
Naphthalene :		
Guideline ACGIH:	ACGIH TWA (ppm) 10 ppm ACGIH STEL (ppm) 15 ppm	
Guideline OSHA:	OSHA PEL (TWA) (mg/m³) 50 mg/m³ OSHA PEL (TWA) (ppm) 10 ppm	
Appropriate engineering controls:		
Engineering Controls:	Ensure good ventilation of the work station. Ventilation should provide 10 air changes per hour.	
Individual protection measures:		
Eye/Face Protection:	Chemical splash goggles. Eyewash station in work area.	
Skin Protection Description:	Wear suitable protective clothing such as coveralls.	
Hand Protection Description:	Protective gloves.	
Respiratory Protection:	Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear appropriate respiratory protection, if occupational exposure limits are exceeded or irritation/sensitivity is experienced.	
PPE Pictograms:	I 🗢 🛉 📀	

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:		
Physical State:	Solid Appearance : Pastilles. Flakes.	
Color:	Pale yellow. Translucent. Amber.	
Odor:	Hydrocarbon.	
Odor Threshold:	No data available	
Boiling Point:	No data available	
Melting Point:	No data available	
Density:	Relative density : 1.06	

		1.08
Solubility:		Water: Insoluble
Vapor Density:		Relative vapor density at 20 °C : No data available
Vapor Pressure:		~ 25 mm Hg
Evaporation Rate:		Relative evaporation rate (butyl acetate=1) : No data available
pH:		No data available
Flash Point:		> 480 °C
Flash Point Method	:	(Closed Cup)
Auto Ignition Temp	erature:	No data available
Explosive Propertie	s:	Explosive limits : No data available
9.2. Other information	tion:	
Notes :		Log Kow : No data available

SECTION 10 : STABILITY and REACTIVITY

Reactivity:	
Reactivity:	No dangerous reactions known under normal conditions of use. Possibility of hazardous reactions : May form combustible dust concentrations in air.
Chemical Stability:	
Chemical Stability:	Stable under use and storage conditions as recommended in section 7.
Conditions To Avoid:	
Conditions to Avoid:	Avoid the build-up of electrostatic charge. High temperature. Avoid dust formation. Direct sunlight. No flames, no sparks. Eliminate all sources of ignition. To avoid thermal decomposition, do not overheat.
Incompatible Materials:	
Incompatible Materials:	Oxidizing agents.
Hazardous Decomposition Products	<u>.</u>
Special Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 : TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:	
Naphthalene :	
Acute Toxicity:	ATE (oral) 500
Acute Toxicity:	Not classified Based on available data, the classification criteria are not met
Naphthalene :	
IARC:	IARC group 2B - Possibly carcinogenic to humans
NTP:	National Toxicology Program (NTP) Status: Reasonably anticipated to be Human Carcinogen
Naphthalene :	
Skin:	LD50 dermal rabbit > 20 g/kg
Inhalation:	LC50 inhalation rat > 340 mg/m ³ (Exposure time: 1 h)
Ingestion:	LD50 oral rat 490 mg/kg
Sensitization:	Respiratory or skin sensitization:Not classified Based on available data, the classification criteria are not met
Mutagenicity:	Germ cell mutagenicity : Not classified Lack of data
Reproductive Toxicity:	Not classified Lack of data

SECTION 12 : ECOLOGICAL INFORMATION

Naphthalene :	
Bioaccumulative potential:	
Bioaccumulation:	BCF fish 1 30 - 430 Log Pow 3.3 (at 20 °C)
Other adverse effects:	
Effect of Material On Aquatic Life:	LC50 fish 1: 5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) EC50 Daphnia 1: 2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna) EC50 other aquatic organisms 1: 0.4 mg/l (Exposure time: 72 h - Species: Skeletonema costatum) LC50 fish 2: 1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through]) EC50 Daphnia 2: 1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])

Ecotoxicity:	Ecology - general : Harmful to aquatic life with long lasting effects.
Persistence and degradability:	
Biodegradation:	No additional information available
<u>Mobility in soil:</u>	
Mobility In Environmental Media:	Mobility in soil : No additional information available

SECTION 13 : DISPOSAL CONSIDERATIONS

Description of waste:	
Waste Disposal:	Waste treatment methods : Transfer to a safe disposal area in accordance with federal, state, and local regulations.
Contaminated Packaging:	Please ensure that packaging, including drums, are disposed of in a responsible manner and in accordance with federal, and your state's, solid/hazardous waste regulations. Due to more restrictive waste disposal regulations, NEVER wastetreat or dispose of material until you check your appropriate local, state, & federal regulations for requirements.
RCRA Number:	Product as purchased is not a RCRA hazardous Waste.
Notes :	USEPA guidelines for the classification determination are found in 40CFR 261.3.


SECTION	14 .	TRANSPORT	INFORMATION
SECTION			

DOT Shipping Name:	Non regulated.
DOT Pictograms:	Not Regulated
IATA Shipping Name:	Non regulated.
IATA Pictograms:	Not Regulated
IMDG Shipping Name :	Non regulated.
ADR Shipping Name :	Non regulated.
RID Shipping Name :	Non regulated.
ICAO Shipping Name:	Non regulated.

SECTION 15 : REGULATORY INFORMATION

Safety, health and	environmental	regulations	specific for the	product:

TSCA Inventory Status:	All components of this product are listed or exempt in TSCA inventory of Chemicals Substances.
CERCLA Section 302:	If an accidental spill occurs, there is no reporting required.
State Regulations:	PA RTK, Ma RTK, NJ RTK: - Listed
Risk Phrases:	R45 - May cause cancer. R52 - Harmful to aquatic organisms.
Safety Phrase:	S36/39 - Wear suitable protective clothing and eye/face protection. S 3 - Keep in a cool, dry place. S29/35 - Do not empty into drains; dispose of this material and its container in a safe way.



Notes :

rd :	1	Health Hazard	1	
	1	Fire Hazard	1	
	0	Reactivity	0	
	J	Personal Protection	J	

Important Note: This information relates to the specific product described herein and may not be valid for this material when used in combination with other raw materials. The information provided is without warranty regarding its accuracy or completeness. The information may not be valid under all conditions. The user has the final responsibility for determining the suitability of the product in a given application.

¥2

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.