

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 04/11/2002

MSDSUSA/ANSI/EN/150000049754/Version 3.0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	Pamak(TM) 1 Tall Oil Fatty Acid
Product Identification Number(s)	75457-00, P7545700, P7545702, P75457SP, P754570A
Manufacturer/Supplier	Eastman Chemical Company, Kingsport, Tennessee 37662
MSDS Prepared by	Eastman Product Safety and Stewardship
Chemical Name	not applicable
Synonym(s)	800487
Molecular Formula	not applicable
Molecular Weight	not applicable
Product Use	industrial chemical
OSHA Status	nonhazardous

For emergency health, safety & environmental information, call 800-EASTMAN.

For emergency transportation information, call CHEMTREC at 800-424-9300 or call 800-EASTMAN.

2. COMPOSITION INFORMATION ON INGREDIENTS

(Typical composition is given, and it may vary. A certificate of analysis can be provided.)

Weight %	Component	CAS Registry No.
100%	distilled tall-oil fatty acids	61790-12-3

3. HAZARDS IDENTIFICATION

LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL

HMIS® Hazard Ratings: Health - 1, Flammability -1, Chemical Reactivity - 0

HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

4. FIRST-AID MEASURES

Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms persist.

Eyes: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention if symptoms persist.

Skin: Wash with soap and water. Get medical attention if symptoms occur.

Ingestion: Seek medical advice.

©COPYRIGHT 2002 BY EASTMAN CHEMICAL COMPANY

Visit our website at www.EASTMAN.com or call 1-800-EASTMAN.

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 04/11/2002

MSDSUSA/ANSI/EN/150000049754/Version 3.0

5. FIRE FIGHTING MEASURES

Extinguishing Media: water spray, dry chemical, carbon dioxide, foam, alcohol foam

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products: carbon dioxide, carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

7. HANDLING AND STORAGE

Personal Precautionary Measures: No special precautionary health measures should be needed under anticipated conditions of use.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials.

Storage: Keep container closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Country specific exposure limits have not been established or are not applicable unless listed below.

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances such as poorly ventilated spaces, evaporation from large surfaces, spraying, heating, etc.

Respiratory Protection: If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: mist

Eye Protection: It is a good industrial hygiene practice to minimize eye contact.

Skin Protection: It is a good industrial hygiene practice to minimize skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: viscous liquid

Color: amber

Odor: fatty

Specific Gravity: 0.91

Vapor Pressure: 20 °C; < 1.33 mbar

Vapor Density: > 1

Melting Point: < 10 °C

Boiling Point: > 350 °C

©COPYRIGHT 2002 BY EASTMAN CHEMICAL COMPANY

Visit our website at www.EASTMAN.com or call 1-800-EASTMAN.

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 04/11/2002

MSDSUSA/ANSI/EN/150000049754/Version 3.0

Viscosity: 30 mPa.s (25 °C)

Solubility in Water: slight

Flash Point: > 148.88 °C (method unspecified)

Autoignition Temperature: 315.55 - 371.11 °C

Thermal Decomposition Temperature: Thermal stability not tested. Low stability hazard expected at normal operating temperatures.

10. STABILITY AND REACTIVITY

Stability:	Stable.
Incompatibility:	Material reacts with strong oxidizing agents.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Inhalation: May cause allergic respiratory reaction.

Skin: May cause allergic skin reaction.

Toxicity data are not available unless listed below.

12. ECOLOGICAL INFORMATION

This material has not been tested for environmental effects.

13. DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Incinerate.

14. TRANSPORT INFORMATION

Marine pollutant components: none unless listed below

DOT (USA): Class not regulated

ICAO Status: Class not regulated

IMDG Status: Class not regulated

15. REGULATORY INFORMATION

©COPYRIGHT 2002 BY EASTMAN CHEMICAL COMPANY

Visit our website at www.EASTMAN.com or call 1-800-EASTMAN.

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 04/11/2002

MSDSUSA/ANSI/EN/150000049754/Version 3.0

WHMIS (Canada) Status: noncontrolled

SARA 313: none, unless listed below

Carcinogenicity Classification (components present at 0.1% or more): none, unless listed below

TSCA (US Toxic Substances Control Act): All components of this product are listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act): All components of this product are listed on the DSL. Any impurities present in this product are exempt from listing.

EINECS (European Inventory of Existing Commercial Chemical Substances): All components of this product are listed on EINECS. Any polymer intentionally present in this product has regulatory clearance under Directives of the European Union.

AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): All components of this product are listed on AICS or otherwise comply with NICNAS.

MITI (Japanese Handbook of Existing and New Chemical Substances): All components of this product are listed in the Handbook or have been approved in Japan by new substance notification.

ECL (Korean Toxic Substances Control Act): All components of this product are listed on the Korean inventory or otherwise comply with the Korean Toxic Substances Control Act.

16. OTHER INFORMATION

Visit our website at www.EASTMAN.com or call 1-800-EASTMAN.

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.

©COPYRIGHT 2002 BY EASTMAN CHEMICAL COMPANY

Visit our website at www.EASTMAN.com or call 1-800-EASTMAN.