



# THE DOW CHEMICAL COMPANY MATERIAL SAFETY DATA SHEET



**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 1 of 15

Dow (hereinafter, and for purposes of this MSDS only, refers to The Dow Chemical Company and to Dow Chemical Canada Inc.) encourages and expects you to read and understand the entire MSDS, as there is important information throughout the document. Dow expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### 1.1 IDENTIFICATION

**Product Name** CARBOWAX(TM) SENTRY(TM) POLYETHYLENE GLYCOL 400  
NF,FCC GRADE

### 1.2 COMPANY IDENTIFICATION

The Dow Chemical Company  
Midland, MI 48674

### 1.3 EMERGENCY TELEPHONE NUMBER

**24-HOUR EMERGENCY TELEPHONE NUMBER: (989)636-4400.**  
Customer Information Number: 1-800-258-2436.

MARKETED BY  
**HARWICK STANDARD**  
**DISTRIBUTION CORPORATION**  
60 S. Seiberling Street • Akron, Ohio 44305

\* or ® Indicates a Trademark of The Dow Chemical Company.

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page 2 of 15**

## 2. COMPOSITION INFORMATION

<b>Component</b>	<b>CAS #</b>	<b>Amount (%W/W )</b>
Polyethylene glycol	25322-68-3	> 99 %

## 3. HAZARDS IDENTIFICATION

### 3.1 EMERGENCY OVERVIEW

<b>Appearance</b>	Colorless
<b>Physical State</b>	Liquid
<b>Odor</b>	Mild
<b>Hazards of product</b>	NO SIGNIFICANT IMMEDIATE HAZARDS FOR EMERGENCY RESPONSE ARE KNOWN.

### 3.2 POTENTIAL HEALTH EFFECTS

#### Effects of Single Acute Overexposure

**Inhalation** At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous.

**Eye Contact** May cause slight temporary eye irritation. Corneal injury is unlikely.

**Skin Contact** Prolonged contact is essentially nonirritating to skin. Material may be handled at elevated temperatures; contact with the heated material may cause thermal burns.

**Skin Absorption** Prolonged skin contact is unlikely to result in absorption of harmful amounts.

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page 3 of 15**

---

**Swallowing** Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

## **Chronic, Prolonged or Repeated Overexposure**

**Other Effects of Overexposure** No information currently available.

See Section 11 for toxicological information and additional information about potential health effects.

## **3.3 POTENTIAL ENVIRONMENTAL EFFECTS**

See Section 12 for Ecological Information.

## **4. FIRST AID PROCEDURES**

### **4.1 INHALATION**

Move person to fresh air; if effects occur, consult a physician.

### **4.2 EYE CONTACT**

Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

### **4.3 SKIN CONTACT**

Wash skin with plenty of water.

### **4.4 SWALLOWING**

No emergency medical treatment necessary.

### **4.5 NOTES TO PHYSICIAN**

If burn is present, treat as any thermal burn, after decontamination.

No specific antidote.

Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

# **MATERIAL SAFETY DATA SHEET**

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page 4 of 15**

## **5. FIRE FIGHTING MEASURES**

### **5.1 FLAMMABLE PROPERTIES - REFER TO SECTION 9, PHYSICAL AND CHEMICAL PROPERTIES**

### **5.2 EXTINGUISHING MEDIA**

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

### **5.3 FIRE FIGHTING PROCEDURES**

Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from a protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

### **5.4 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS**

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, pants, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

### **5.5 UNUSUAL FIRE AND EXPLOSION HAZARDS**

Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

### **5.6 HAZARDOUS COMBUSTION PRODUCTS**

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

## **6. ACCIDENTAL RELEASE MEASURES**

**Steps to be Taken if Material is Released or Spilled:**

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 5 of 15

Contain spilled material if possible. Small spills: Dilute with large quantities of water. Large spills: Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations for additional information.

**Personal Precautions:** Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**Environmental Precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

## **7. HANDLING AND STORAGE**

### **7.1 HANDLING**

#### **General Handling**

See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

#### **Ventilation**

Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

#### **Other Precautions**

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

### **7.2 STORAGE**

Use product promptly after opening. Store in the following material(s): stainless steel. polypropylene. polyethylene lined container. Teflon. glass-lined container. Plasite 3066 lined container. Plasite 3070 lined container. 316 stainless steel.

## **8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

### **8.1 EXPOSURE LIMITS**

<b>Component</b>	<b>Exposure Limits</b>	<b>Skin Form</b>
Polyethylene glycol	10 mg/m3 TWA8 AIHA WEEL	Aerosol

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page 6 of 15**

*In the Exposure Limits Chart above, if there is no specific qualifier (i.e., Aerosol) listed in the Form Column for a particular limit, the listed limit includes all airborne forms of the substance that can be inhaled.*

*A "Yes" in the Skin Column indicates a potential significant contribution to overall exposure by the cutaneous (skin) route, including mucous membranes and the eyes, either by contact with vapors or by direct skin contact with the substance. A "Blank" in the Skin Column indicates that exposure by the cutaneous (skin) route is not a potential significant contributor to overall exposure.*

## **8.2 PERSONAL PROTECTION**

- Respiratory Protection:** Atmospheric levels should be maintained below the exposure guideline.  
When airborne exposure guidelines and/or comfort levels may be exceeded, use an approved air-purifying respirator.
- Ventilation:** Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.
- Eye Protection:** Use safety glasses.
- Other Protective Equipment:** No precautions other than clean body-covering clothing should be needed.  
Use gloves with insulation for thermal protection, when needed.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical State:** Liquid

**Appearance:** Colorless

**Odor:** Mild

**Flash Point - Closed Cup:** 227 °C 440 °F *Pensky-Martens Closed Cup ASTM D 93*

### **Flammable Limits In Air:**

Lower *Not determined. Non-volatile material.*  
Upper *Not determined. Non-volatile material.*

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page 7 of 15**

**Autoignition Temperature:** *No test data available.*

**Vapor Pressure:** < 0.01 mmHg 20 °C

**Boiling Point (760 mmHg):** > 200 °C > 392 °F Decomposes

**Vapor Density (air = 1):** > 10

**Specific Gravity (H2O = 1):** 1.1 20 °C / 20 °C

**Freezing Point:** 4 - 8 °C 39 - 46 °F

**Melting Point:** *Not applicable.*

**Solubility in Water (by weight):** 100 % 20 °C

**pH:** *No test data available.*

**Molecular Weight:** 380 - 420 g/mol

**Percent Volatiles:** 0.3 Wt%

## **10. STABILITY AND REACTIVITY**

**10.1 STABILITY/INSTABILITY** Thermally stable at typical use temperatures.

**Conditions to Avoid:** Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

**Incompatible Materials:** Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

**Thermal Decomposition:** Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon dioxide. Alcohols. Ethers. Hydrocarbons. Ketones. Polymer fragments.

**10.2 HAZARDOUS POLYMERIZATION** Will not occur.

# **MATERIAL SAFETY DATA SHEET**

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page 8 of 15**

---

## **11. TOXICOLOGICAL INFORMATION**

### **ACUTE TOXICITY**

#### **Peroral**

Rat; LD50 = > 30000 mg/kg

#### **Percutaneous**

Rabbit; LD50 = > 20000 mg/kg

#### **Inhalation**

Vapor Study, 8 hr exposure, at room temperature Rat; LC50 = > 13 ppm; The concentration specified represents the highest concentration achievable under the test conditions.

### **SENSITIZATION (ANIMAL AND HUMAN STUDIES)**

Did not cause allergic skin reactions when tested in humans.

### **DEVELOPMENTAL TOXICITY**

For similar material(s), Did not cause birth defects in laboratory animals.

### **CHRONIC TOXICITY AND CARCINOGENICITY**

Did not cause cancer in laboratory animals.

### **GENETIC TOXICOLOGY**

#### **In Vitro**

In vitro mutagenicity studies were negative.

#### **In Vivo**

For similar material(s), Animal mutagenicity studies were negative.

### **SIGNIFICANT DATA WITH POSSIBLE RELEVANCE TO HUMANS**

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.



# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 9 of 15

## 12. ECOLOGICAL INFORMATION

### 12.1 ENVIRONMENTAL FATE

Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%).

#### BOD (% Oxygen consumption)

	Day 5	Day 10	Day 15	Day 20	Day 28/30
	5 - 17 %	34.5 - 38 %		40.2 - 70 %	

### 12.2 ECOTOXICITY

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50 >100 mg/L in most sensitive species tested).

#### Toxicity to Aquatic Invertebrates

water flea Daphnia magna; LC50

**Result value:** 53000 mg/l

#### Toxicity to Fish

fathead minnow (Pimephales promelas); LC50

**Result value:** 87000 mg/l

### 12.3 FURTHER INFORMATION

No bioconcentration is expected because of the relatively high water solubility.

Chemical Oxygen Demand (COD) - calculated:: 1.81 mg/mg

Theoretical Oxygen Demand (THOD) - calculated:: 1.74 mg/mg

## 13. DISPOSAL CONSIDERATIONS

## **MATERIAL SAFETY DATA SHEET**

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 10 of 15

### **13.1 DISPOSAL**

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. DOW HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION 2 (Composition/ Information On Ingredients). FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: recycler. reclaimer. incinerator or other thermal destruction device. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details .

## **14. TRANSPORT INFORMATION**

### **14.1 U.S. D.O.T.**

#### **NON-BULK**

**Proper Shipping Name :** NOT REGULATED

#### **BULK**

**Proper Shipping Name :** NOT REGULATED

*This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.*

## **15. REGULATORY INFORMATION**

### **15.1 FEDERAL/NATIONAL**

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page 11 of 15**

---

## OSHA HAZARD COMMUNICATION STANDARD

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

---

## SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT) SECTION 313

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

---

## SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT) SECTION 302

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

---

## SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT) SECTIONS 311 AND 312

**Delayed (Chronic) Health Hazard :** No  
**Fire Hazard :** No  
**Immediate (Acute) Health Hazard :** No  
**Reactive Hazard :** No  
**Sudden Release of Pressure Hazard :** No

## TOXIC SUBSTANCES CONTROL ACT (TSCA)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

---

## EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS)

The components of this product are on the EINECS inventory or are exempt from EINECS inventory requirements.

---

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 12 of 15

---

## CEPA - DOMESTIC SUBSTANCES LIST (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

---

## 15.2 STATE/LOCAL

### PENNSYLVANIA (WORKER AND COMMUNITY RIGHT TO KNOW ACT): PENNSYLVANIA HAZARDOUS SUBSTANCES LIST AND/OR PENNSYLVANIA ENVIRONMENTAL HAZARDOUS SUBSTANCE LIST:

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

---

### PENNSYLVANIA (WORKER AND COMMUNITY RIGHT TO KNOW ACT): PENNSYLVANIA SPECIAL HAZARDOUS SUBSTANCES LIST:

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

---

### CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

<b>Component</b>	<b>CAS #</b>	<b>Amount</b>
Acetaldehyde	75-07-0	<= 0.0006%
1,4-Dioxane	123-91-1	<= 0.0005%
Formaldehyde	50-00-0	<= 0.0004%
Ethylene oxide	75-21-8	<= 0.0005%

---

### CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

<b>Component</b>	<b>CAS #</b>	<b>Amount</b>
Ethylene oxide	75-21-8	<= 0.0005%

---

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 13 of 15

## CALIFORNIA SCAQMD RULE 443.1 (SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT RULE 443.1, LABELING OF MATERIALS CONTAINING ORGANIC SOLVENTS)

**VOC:** Vapor pressure <0.01 mmHg at 20°C  
2 g/l  
2 g/l of material less water and less exempted solvents.

*This section provides selected regulatory information on this product including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.*

## **16. OTHER INFORMATION**

### **16.1 ADDITIONAL INFORMATION**

Additional information on this product may be obtained by calling Dow's Customer Information Group at 1-800-258-2436 (U.S.) or 1-800-331-6451 (Canada).

### **16.2 HAZARD RATING SYSTEM**

**NFPA ratings for this product are: H - 0      F - 1      R - 0**

*These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.*

### **16.3 RECOMMENDED USES AND RESTRICTIONS**

#### **FOR INDUSTRY USE ONLY**

A partial list of examples include pharmaceutical products, personal care products, automotive products, household products, packaging products, petroleum chemicals, plastics, inks, coatings, adhesives, chemical intermediates, rubber processing, lubricants, metalworking fluids, mold release agents, ceramics, and wood treating.

# MATERIAL SAFETY DATA SHEET

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 14 of 15

---

This product has clearances under FDA Food Additive Regulations. It is the responsibility of the user of this product as a Direct or Indirect Food Additive to read and understand all applicable FDA regulations in Title 21 of the Code of Federal regulations as well as any other applicable regulations.

**CAUTION!** For food, feed, drug or cosmetic applications, use CARBOWAX(TM) SENTRY(TM) brands, N.F., F.C.C. Grade. Only SENTRY brand products are tested to meet N.F. and F.C.C. standards for these applications.

Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group at 1-800-258-2436 (U.S.) or 1-800-331-6451 (Canada) for more information.

## 16.4 REVISION

Version: 6.

Revision: 05/20/2002

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

## 16.5 LEGEND

Bacterial/NA	Non Acclimated Bacteria
F	Fire
H	Health
IHG	Industrial Hygiene Guideline
N/A	Not available
NFPA	National Fire Protection Association
O	Oxidizer
R	Reactivity
TS	Trade secret
VOL/VOL	Volume/Volume
W	Water Reactive
W/W	Weight/Weight

*NOTICE: Dow urges each customer or recipient of this MSDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this MSDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given., Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that its activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product*

## **MATERIAL SAFETY DATA SHEET**

**Product Name:** CARBOWAX(TM) SENTRY(TM)  
POLYETHYLENE GLYCOL 400 NF,FCC GRADE  
**MSDS#:** 468

**Effective Date:** 05/20/2002

**Page** 15 of 15

---

*are not under the control of Dow, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product., Due to the proliferation of sources for information such as manufacturer-specific MSDSs, Dow is not and cannot be responsible for MSDSs obtained from any source other than Dow. If you have obtained a Dow MSDS from a non-Dow source or if you are not sure that a Dow MSDS is current, please contact Dow for the most current version.*