

## MATERIAL SAFETY DATA SHEET

# STAN-TONE 90SMB04 BLACK

Version Number 1.0 Revision Date 04/02/2003 Page 1 of 7 Print Date 5/13/2003

## 1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY

Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

or accident).

Product name

number

STAN-TONE 90SMB04 BLACK

Product code

FO2000090460

Chemical Name

: Mixture : Mixture

CAS-No. Product Use

: Industrial Applications

## 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %	
Calcium carbonate	1317-65-3	5 - 10	
Quartz	14808-60-7	5 - 10	
Carbon black	1333-86-4	30 - 60	
Silica, amorphous	7631-86-9	30 - 60	

## 3. HAZARDS IDENTIFICATION

## **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation

: Resin particles, like other inert materials, can be mechanically

irritating.

Ingestion

: May be harmful if swallowed.

Eyes

: Resin particles, like other inert materials, are mechanically irritating to

eyes.

Skin

: Experience shows no unusual dermatitis hazard from routine handling.

MARKETED BY
HARWICK STANDARD
DISTRIBUTION CORPORATION
60 S. Seiberling Street • Akron, Ohio 44305



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE 90SMB04 BLACK

Version Number 1.0 Revision Date 04/02/2003

Page 2 of 7 Print Date *5/13/2003* 

Chronic exposure

: Refer to Section 11 for Toxicological Information.

**Medical Conditions** 

Aggravated by Exposure:

None known.

## 4. FIRST AID MEASURES

Inhalation

Ingestion

: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin

Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

## 5. FIRE-FIGHTING MEASURES

Flash point

: Not applicable

Flammable Limits

Upper explosion limit Lower explosion limit

Not applicable Not applicable Not relevant

Autoignition temperature Suitable extinguishing media

Water spray, dry powder, foam, carbon dioxide (CO2).

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: None

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions

Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up

: Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section

13 of this MSDS for proper disposal methods.

# 7. HANDLING AND STORAGE



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE 90SMB04 BLACK

Version Number 1.0 Revision Date 04/02/2003

Page 3 of 7 Print Date 5/13/2003

Handling

Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Storage

Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

: No personal respiratory protective equipment normally required when

handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this

material.

Eye/Face Protection

Safety glasses with side-shields.

Hand protection

Protective gloves.

Skin and body protection

Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety

practice. Wash hands before breaks and at the end of workday.

Engineering measures

Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be

necessary to minimize employee exposure to processing vapors.

## Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
Carbon black	3.5 mg/m3	PEL:	Total dust, as carbon black	OSHA Z1
Quartz	0.05 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH
Quartz	0.098 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
	0.29 mg/m3	Time Weighted Average (TWA):	Total dust.	MX OEL
	0.05 mg/m3	Time Weighted Average (TWA):		ACGIH



# MATERIAL SAFETY DATA SHEET

# STAN-TONE 90SMB04 BLACK

Version Number 1.0 Revision Date 04/02/2003

Page 4 of 7 Print Date 5/13/2003

Quartz		Time Weighted Average (TWA):		MX OEL
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Color
Odor

Melting point/range

: Solid: Pellets, slabs, sheets: BLACK

Characteristic rubber odor V
Not determined V

Bulk density Vapor pressure Vapor density pH

Evaporation rate

Specific Gravity

Not applicable.Not determinedNot establishedNot applicableNot applicable

Not applicable

Boiling Point: : Not applicable Water solubility : Insoluble

## 10. STABILITY AND REACTIVITY

Stability

Stable.

Hazardous Polymerization

Will not occur.

Conditions to avoid

Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials

: Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

## **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ	
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.	
		Systemic effects	Eyes, Skin, Respiratory system.	
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.	
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.	
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.	

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE 90SMB04 BLACK

Version Number 1.0 Revision Date 04/02/2003

Page 5 of 7 Print Date *5/13/2003* 

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

#### Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

# NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

# Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

## 12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

**Environmental Toxicity** 

Chemicals are not readily available as they are bound within the

matrix of the polymer.

Bioaccumulation Potential

Chemicals are not readily available as they are bound within the

matrix of the polymer.

Additional advice

Not applicable

## 13. DISPOSAL CONSIDERATIONS

Product

Where possible, recycling is preferred to disposal or incineration.



## MATERIAL SAFETY DATA SHEET

# STAN-TONE 90SMB04 BLACK

Version Number 1.0 Revision Date 04/02/2003

Page 6 of 7 Print Date *5/13/2003* 

The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging

Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

## 14. TRANSPORT INFORMATION

U.S. DOT Classification

Not regulated for transportation.

ICAO/IATA

: Not regulated for transportation.

IMO / IMDG

: Not regulated for transportation.

## 15. REGULATORY INFORMATION

US Regulations:

**OSHA Status** 

Classified as hazardous based on components.

TSCA Status

All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition

65

WARNING! This product contains a chemical known to the State of

California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable

Canadian Regulations:



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE 90SMB04 BLACK

Version Number 1.0 Revision Date 04/02/2003

Page 7 of 7 Print Date 5/13/2003

WHMIS Classification

: D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1333-86-4	
14808-60-7	
7631-86-9	
109-86-4	

DSL

All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS

Listed.

China IECS

Listed.

Europe EINECS

Not determined.

Japan ENCS

Not determined.

Korea KECI

Listed.

Philippines PICCS

: Listed.

## 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.