



CILBOND[®] 4000 Diluent TECHNICAL DATA SHEET

CILBOND 4000 Diluent is used for diluting Cilbond 40 series products. It consists of a blend of solvents.

BENEFITS OF CILBOND 4000 Diluent

- Ready to use solvent blend reduces inventory.
- Formulated to improve spray application of Cilbond 40 series products.
- Helps reduce or eliminate cobwebbing and dry spray.
- It can also be used with **Cilbond 36**.

APPLICATION:

- Consult individual Cilbond 40 series technical data sheets for dilution ratios.
- Slowly add **Cilbond 4000 Diluent** to the Cilbond 40 series product whilst stirring. This will prevent any destabilisation, gelling or shocking of the blend.
- Ensure the diluted Cilbond is fully homogenous during use.

TYPICAL PHYSICAL PROPERTIES OF CILBOND 4000 Diluent

Appearance	Clear
Non-Volatile Solids	0%
Specific Gravity @ 26°C (79°F)	0.82
Flash Point (Abel Pensky)	-6°C (21°F)
Solvent Type	Methyl Ethyl Ketone (MEK), Acetate, Ester
Shelf Life	24 months from date of manufacture

PACKAGING

Cilbond 4000 Diluent is supplied in 25L and 200L containers.

FURTHER INFORMATION

For more information on **Cilbond 4000 Diluent** or for details of our other products please visit www.cilbond.com or e-mail sales@cilbond.com