



DAIKIN AMERICA, INC.
20 Olympic Drive
Orangeburg, NY 10962
Tel: (845) 365-9500
Fax: (845) 365-9515

TECHNICAL DATA SHEET

DAIKIN PTFE F-104U

Daikin PTFE F-104U is a high molecular weight polytetrafluoroethylene fine powder resin for paste extrusion manufactured without the use of PFOA. F-104U has been specifically designed for the manufacture of unsintered tapes, sintered tapes and tubing at low reduction ratios.

Typical characteristics of the resin are as follows:

CHARACTERISTIC	UNITS	TYPICAL VALUE	TEST METHOD
BULK DENSITY (MIN.)	g/l	400	ASTM D 4895
STD SPECIFIC GRAVITY	---	2.155 - 2.185	ASTM D 4895
TENSILE STRENGTH (MIN.)	MPa	25	ASTM D 4895
ELONGATION (MIN.)	%	300	ASTM D 4895
PARTICLE SIZE	Microns	400 - 650	ASTM D 4895
EXTRUSION PRESSURE	kg/cm ²	100 - 180	DAIKIN qac213fp
APPEARANCE	---	WHITE POWDER	VISUAL

Note: The data listed above fall within the normal range of product, but they should not be used to establish specification limits nor be used as the sole basis of design.

SAFETY & HANDLING

Daikin PTFE F-104U should be handled like other Daikin PTFE resins. When PTFE resins are heated to temperatures above 260°C, minor amounts of decomposition products are given off. These decomposition products may be harmful and inhalation of these fumes must be avoided. Ovens, process equipment and the working area must be adequately ventilated. For further information please refer to the material safety data sheet for this product.

Rev. 05/2010