

PRODUCT BULLETIN

DUOPRIME[®] OIL 350 WHITE MINERAL OIL, USP

| Property | Method | Specifications | Typical Value |
|---------------------------|--------------|----------------|---------------|
| Viscosity at 40°C, cSt | D445 | 64.5 - 70.0 | 67.5 |
| Viscosity at 100°F, SUS | D2161 | 338 - 364 | 350 |
| Viscosity at 100°C, cSt | D445 | | 8.7 |
| Specific Gravity, 25/25°C | D4052 | 0.855 - 0.881 | 0.867 |
| API Gravity, ° | D4052 (calc) | 28.3 - 33.1 | 30.7 |
| Color, Saybolt | D156 | +30, min | +30 |
| Pour Point, °F | D97 | +20, max | +10 |
| Flash Point, °F | D92 | 445, min | 450 |
| 21 CFR 172.878 | CFR | Pass | Pass |
| USP/NF | USP/NF | Pass | Pass |

Duoprime[®] Oil 350 is certified to meet the requirements of the United States Pharmacopeia (current revision) and the following FDA regulations:

- 21 CFR 172.878 Direct use in food
- 21 CFR 178.3620(a) Indirect use in food
- 21 CFR 573.680 Use in animal feed

Duoprime[®] Oil 350 is NSF H1, 3H registered and meets the USDS 1998 H1, 3H guidelines for use in USDS inspected meat and poultry plants. Duoprime[®] 350 is certified to ANSI/NSF Standard 60, Drinking Water Treatment Chemicals - health effects for use with potable water systems. It is produced under Kosher Supervision of the Kashruth division of the Union of Orthodox Jewish Congregations of America.

SCHUMANN/STEIER, INC EXPRESSLY DISCLAIMS ANY WARRANTIES OF MERCHANTABILITY OR FITNESS, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF DUOPRIME[®] OIL 350 FOR USE IN ANY SECONDARY PRODUCTS INCLUDING THE ACTUAL RESULTS OF ITS USE IN ANY SUCH PRODUCTS. SCHUMANN/STEIER, INC ALSO EXPRESSLY DISCLAIMS THE ABOVE WARRANTIES RESULTING FROM THE USE OF THIS PRODUCT OR ANY SAMPLE OF THIS PRODUCT IN ANY SECONDARY PRODUCTS.

> MARKETED BY HARWICK STANDARD DISTRIBUTION CORPORATION 60 S. Seiberling Street • Akron. Ohio 44305

42015