



# TECHNICAL DATA SHEET

Neville Chemical Company  
2800 Neville Road  
Pittsburgh, PA 15225-1496

Phone: 412-777-4210  
E-Mail: support@nevchem.com  
Internet: www.nevchem.com

LX<sup>®</sup>-1055

## PRODUCT DESCRIPTION

LX<sup>®</sup>-1055 is a thermoplastic low molecular weight, hydrocarbon resin produced by thermal polymerization of mixed DCPD, aromatic and alicyclic monomers derived from petroleum feedstocks.

## APPLICATIONS / END USES

- Rubber Tires, Hoses and Belts
- Asphalt Roof Coatings
- Peel and Stick Roofing Membranes

## ATTRIBUTES / BENEFITS

- Processing and Dispersing Aid
- Promotes Wetting of Pigments and Fillers
- Reduces Mixing Energy
- Improves Properties in Cured Rubber
- Hydrophobic
- Low Molecular Weight

## PROPERTIES

Property	Test Method	Typical Value	Specifications
Softening Point, R&B °C	ASTM E28	105	105 ± 5
Gardner Color (50% in 100 Solvent)	ASTM D1544	13	18 Max.
Iodine Number	ASTM D1959	140	NA
Specific Gravity @ 25°C	ASTM D71	1.09	NA
Brookfield Viscosity, cps @ 130°C @ 150°C @ 170°C	ASTM 3236	26,600 3,700 970	NA
Molecular Weight Mn Mw	ASTM D5290	430 1,030	NA
Appearance	Visual	Dark Amber Color Flakes	NA

**PACKAGING:** LX-1055 resin is packaged in 50 lb. (22.7/kg.) bags or super sacks

Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.

Revised: February 1, 2023