



TECHNICAL DATA SHEET

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

Phone: 412-777-4210
E-Mail: support@nevchem.com
Internet: www.nevchem.com

NP-25 Liquid Hydrocarbon Resin

PRODUCT DESCRIPTION

NP-25 resin is a low molecular weight liquid resin produced by catalytic polymerization of mixed aromatic and cyclo-aliphatic petroleum derived feed stocks.

APPLICATIONS / END USES

- Self Adhered Roofing Membranes
- SBR-Based Mastic Adhesives
- Rubber Compounding
- Lithoink Pigment Dispersions
- High Solids alkyd-based Coatings
- Waterproofing

ATTRIBUTES / BENEFITS

- Enhances Pigment Wetting
- Improved Filler Dispersion
- Induces Flow and Leveling
- Improves Tack
- Plasticizes
- Viscosity Reduction

PROPERTIES

Property	Test Method	Typical Value	Specifications
Softening Point, R&B °C	ASTM E28	25	25 ± 5
Gardner Color (50% in 100 Solvent)	ASTM D1544	11	16 Max.
Specific Gravity @ 25°C	ASTM D71	1.01	N/A
Brookfield Viscosity @ 120°F, cps	ASTM 3236	12,000	N/A
Flash Point, °F (COC)	ASTM D92	400	N/A
Appearance		Amber Viscous Liquid	

PACKAGING: NP-25 Resin is shipped in drums, 410 pounds net weight, or heated bulk transport.

TSCA Status: Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.

Revised: 8/27/15