

5955 Scenic Highway • Baton Rouge, LA 70805-2044 800 / 535-9960 • www.lioncopolymer.com

Royalene[®] 525 EPDM

Product Data

" An Ultra Fast Curing Polymer for Automotive Extrusions "

Unique Features

- ► High unsaturation Ultra fast cure rate
- Excellent compression set resistance in closed cell sponge extrusions
- Excellent low temperature properties
- Co-cures well with SBR
- Non-staining
- Friable bale form for rapid mixing in internal mixers and excellent
- dispersion properties
- Excellent weathering resistance

Applications

- Closed cell sponge profile extrusions
- Closed cell sheet sponge
- Automotive window channel extrusions

Raw Polymer Properties and Specifications

	Test Method*	Min.	Max.	Typical
Mooney Viscosity, ML (1+4)/125°C (Unmilled)	ZS 1220B	60	70	—
E/P Weight Ratio	ZS 1231	—	_	60/40
ENB, Weight %	ZS 1222	—	_	8.1
Molecular Weight Distribution	ZS 1296A	—	_	Medium
Volatile Matter, Weight %	ZS 1008K	—	0.7	—
Stabilizer	—	—	_	Non-Staining
Specific Gravity, g/cc	ASTM D-792	_	_	0.86
Color	ZS 1072A		—	Light Amber
Physical Form, lbs/bale	—	_	_	55.1 (25 kg)
				(Friable bale)

* Company Test Methods R-525/mef

ASP-3709H tlj/rfo-04/13

Notice: All information supplied by or on behalf of Lion Copolymer in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Lion Copolymer assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use made of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Lion Copolymer for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the application, processing or use the application or products by the buyer.

harwickstandard.com

Marketed By Harwick Standard Distribution Corporation