

Therm-Chek® 6-V-6A

Stabilizer Product Profile

Product Description

Therm-Chek® 6-V-6A is a liquid barium-cadmium-zinc heat stabilizer for use in plastisols and organisols. It is formulated to perform in both clear and opaque applications and is the industry standard for coil coated applications.

Typical applications include coil coating for aluminum siding, and dip molded plastisol products.

Therm-Chek® 6-V-6A has excellent early color retention and long-term heat stability in both regular and low soap dispersion resins.

Recommended for outdoor applications, Therm-Chek® 6-V-6A has outstanding light stability. It is a proven performer with twenty-five years of field history.

This product has good heat stability when heat sensitive pigments are used.

Safety and Handling

Complete toxicity and handling information can be found on the Material Safety Data Sheet, which is available on request.

Typical Properties

Refractive Index @ 25°C	1.4917
Specific Gravity (25°C)	1.0361
Density (lbs./gal.)	8.62
Color (Gardner)	2
Viscosity (Gardner)	A-3

VALTRIS SPECIALTY CHEMICALS 7500 E. Pleasant Valley Rd. Independence, Ohio 44131 Phone (216) 875-7200 Fax (216) 875-7201 5/21/2012; r 2/15/2016

The information contained in this data sheet has been determined through the application of accepted engineering practice and is believed to be reliable Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of this information, the results to be obtained from the use of the product, so that such use will not infringe on any patent This information is furnished with the express condition that you will make your own tests to



harwickstandard.com