

Therm-Chek® RC 609L

Stabilizer Product Profile

Product Description

Therm-Chek® RC 609L is a zinc, epoxidized soybean oil, liquid heat stabilizer for use in flexible PVC and plastisols. It was specially designed to perform in flooring clearcoats, where initial color and clarity are critical.

Therm-Chek® RC 609L recommended use levels range from 2.0 to 4.0 phr, with 3 to 5 phr of epoxidized soybean oil, depending on application.

Safety and Handling

Complete toxicity and handling information can be found on the Material Safety Data Sheet, which is available on request.

Typical Properties

Physical State	Clear liquid
Color (Gardner)	1
Specific Gravity	0.970
Viscosity (Gardner)	А

VALTRIS SPECIALTY CHEMICALS 7500 E. Pleasant Valley Rd. Independence, Ohio 44131 Phone (216) 875-7200 Fax (216) 875-7201 2/12/2014; r 2/15/16

The information contained in this data sheet has been determined through the application of accepted engineering practice and is believed to be reliable Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of this information, the results to be obtained from the use of the product, so that such use will not infringe on any patent This information is furnished with the express condition that you will make your own tests to



harwickstandard.com