

MATERIAL SAFETY DATA SHEET

Revision Date: 02/15/2006

MSDSUSA/ANSI/EN/150000050559/Version 4.0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	Piccotac(TM) 1098 Hydrocarbon Resin	
Product Identification Number(s)	P7600501	
Manufacturer/Supplier	Eastman Chemical Resins Inc.	
	200 South Wilcox Drive	
	Kingsport, TN 37660-5280	
	US	
	+14232292000	
MSDS Prepared by	Eastman Product Safety and Health	
Chemical Name	hydrocarbon resin	
Synonym(s)	76005-00 800935	
Molecular Formula	not applicable	
Molecular Weight	not applicable	
Product Use	adhesive, coatings, plastic additive	
OSHA Status	nonhazardous	

For emergency health, safety & environmental information, call 800-EASTMAN.

For emergency transportation information, call CHEMTREC at 800-424-9300 or call 800-EASTMAN.

2. COMPOSITION INFORMATION ON INGREDIENTS

(Typical composition is given, and it may vary. A certificate of analysis can be provided, if available.)

Weight % 99.9% 0.1% Component hydrocarbon resin additive(s) CAS Registry No. proprietary proprietary

3. HAZARDS IDENTIFICATION

LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL

HMIS® Hazard Ratings:

Health - 1, Flammability -1, Chemical Reactivity - 0

HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

4. FIRST-AID MEASURES

Inhalation: Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist.
Eyes: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention if symptoms occur. If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Get medical attention.

Skin: Wash with soap and water. If skin irritation or an allergic skin reaction develops, get medical

©COPYRIGHT 2006 BY EASTMAN CHEMICAL COMPANY

Visit our website at www.EASTMAN.com or call 001-423-229-2000.

Page 1

MARKETED BY

HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. Seiberling Street • Akron, Ohio 44305

MATERIAL SAFETY DATA SHEET

Revision Date: 02/15/2006

MSDSUSA/ANSI/EN/150000050559/Version 4.0

attention. If burned by contact with molten material, cool as quickly as possible. Do not peel material from skin. Get medical attention.

Ingestion: Seek medical advice.

Note to Physicians: Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

5. FIRE FIGHTING MEASURES

Extinguishing Media: water spray, dry chemical

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products: carbon dioxide, carbon monoxide

Unusual Fire and Explosion Hazards: Powdered material may form explosive dust-air mixtures.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate personal protective equipment. Shovel up and place in a container for salvage or disposal.

For Large Spills: Flush spill area with water spray. Prevent runoff from entering drains, sewers, or streams.

7. HANDLING AND STORAGE

Personal Precautionary Measures: No special precautionary health measures should be needed under anticipated conditions of use. Avoid contact with molten material.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials. Minimize dust generation and accumulation. In the United States of America, refer to NFPA® Pamphlet No. 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries."

Storage: Keep container tightly closed in a cool, well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Country specific exposure limits have not been established or are not applicable unless listed below.

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances; such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: dust

Eye Protection: It is a good industrial hygiene practice to minimize eye contact. Wear a face shield

MATERIAL SAFETY DATA SHEET

Revision Date: 02/15/2006

MSDSUSA/ANSI/EN/150000050559/Version 4.0

when working with molten material.

Skin Protection: It is a good industrial hygiene practice to minimize skin contact., When material is

heated, wear gloves to protect against thermal burns.

Recommended Decontamination Facilities: eye bath, washing facilities

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: solid (pellet), liquid (molten)

Color: light yellow Odor: slight

Specific Gravity: 0.92 (25 °C) Softening Point: 98 - 102 °C Solubility in Water: negligible

Flash Point: 232 °C (Cleveland open cup)

Thermal Decomposition Temperature: Thermal stability not tested. Low stability hazard expected

at normal operating temperatures.

10. STABILITY AND REACTIVITY

Stability: Not fully evaluated. Materials containing similar structural groups

are normally stable.

Incompatibility: Material reacts with strong oxidizing agents.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

12. ECOLOGICAL INFORMATION

Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

This material has not been tested for environmental effects.

13. DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Incinerate. Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. TRANSPORT INFORMATION

MATERIAL SAFETY DATA SHEET

Revision Date: 02/15/2006

MSDSUSA/ANSI/EN/150000050559/Version 4.0

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.

DOT (USA)

Class 9, Packing Group III when liquid is offered for transport or is transported, in bulk packaging, at or above 100°C and below its flash point; otherwise, not regulated.

Possible Shipping Description(s):

Elevated temperature liquid, n.o.s. 9 UN 3257 III

Sea - IMDG (International Maritime Dangerous Goods)

Class 9, Packing Group III when liquid is offered for transport or is transported at or above 100°C and below its flash point; otherwise, not regulated.

Possible Shipping Description(s):

not regulated

Air - ICAO (International Civil Aviation Organization)

Class Forbidden on aircraft when liquid is offered for transport or is transported at or above 100°C and below its flash point; otherwise, not regulated.

Possible Shipping Description(s):

not regulated

15. REGULATORY INFORMATION

SARA 313: none, unless listed below

Carcinogenicity Classification (components present at 0.1% or more): none, unless listed below

MATERIAL SAFETY DATA SHEET

Revision Date: 02/15/2006

MSDSUSA/ANSI/EN/150000050559/Version 4.0

- TSCA (US Toxic Substances Control Act): This product is listed on the TSCA inventory. Any impurities present in this product are exempt from listing.
- DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act):

 This product is listed on the DSL. Any impurities present in this product are exempt from listing.
- **EINECS (European Inventory of Existing Commercial Chemical Substances):** This product is listed on EINECS or otherwise complies with EINECS requirements. Any polymer present in this product has regulatory clearance under Directives of the European Union.
- AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): This product is listed on AICS or otherwise complies with NICNAS.
- MITI (Japanese Handbook of Existing and New Chemical Substances): This product is listed in the Handbook or has been approved in Japan by new substance notification.
- **ECL (Korean Toxic Substances Control Act):** This product is listed on the Korean inventory or otherwise complies with the Korean Toxic Substances Control Act.
- Phillipines Inventory (PICCS): This product is listed on the Philippine Inventory or otherwise complies with PICCS.
- Inventory of Existing Chemical Substances in China: All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

16. OTHER INFORMATION

Visit our website at www.EASTMAN.com or call 001-423-229-2000.

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.

Highlighted areas indicate new or changed information.