

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	Epolene(TM) C-13 Wax
Product Identification Number(s)	C-13, P0481706, P0481708, P0481709, P0481710, P0481712, P0481713, P0481714, P0481715, P0481717, P0481718, E0481701
Manufacturer/Supplier	Westlake Longview Corporation 2801 Post Oak Blvd. Houston, TX 77056 US
MSDS Prepared by	Product Safety and Health
Chemical Name	ethene, homopolymer
Synonym(s)	04817-00 117477
Molecular Formula	not applicable
Molecular Weight	not applicable
Product Use	wax
OSHA Status	nonhazardous

For emergency health, safety and environmental information, telephone (903) 237-5189.

For emergency transportation information, telephone CHEMTREC at 800-424-9300.

### 2. COMPOSITION INFORMATION ON INGREDIENTS

(Typical composition is given, and it may vary. A certificate of analysis can be provided, if available.)

Weight % 100% Component polyethylene CAS Registry No. 9002-88-4

# 3. HAZARDS IDENTIFICATION

CAUTION! MOLTEN MATERIAL WILL PRODUCE THERMAL BURNS

HMIS® Hazard Ratings: Health - 1, Flammability -1, Chemical Reactivity - 0

HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

# 4. FIRST-AID MEASURES

**Inhalation:** If symptomatic, move to fresh air. Get medical attention if symptoms persist. **Eyes:** If molten material contacts the eye, immediately flush with plenty of water for at least 15

For other information, contact Westlake Chemical Corporation Customer Service 1-800-545-9577 (Monday-Friday, 7:30am-5:00pm - central standard time)

Page 1

MARKETED BY HARWICK STANDARD DISTRIBUTION CORPORATION 60 S. Seiberling Street • Akron, Ohio 44305



minutes. Get medical attention immediately.

- Skin: If burned by contact with molten material, cool as quickly as possible. Do not peel material from skin. Get medical attention.
- **Ingestion:** Seek medical advice. Material is not expected to be absorbed from the gastrointestinal tract so that induction of vomiting should not be necessary.
- Note to Physicians: Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

#### 5. FIRE FIGHTING MEASURES

Extinguishing Media: water spray, carbon dioxide, dry chemical Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Hazardous Combustion Products: carbon dioxide, carbon monoxide Unusual Fire and Explosion Hazards: Powdered material may form explosive dust-air mixtures.

### 6. ACCIDENTAL RELEASE MEASURES

Sweep up and place in a clearly labeled container for chemical waste.

### 7. HANDLING AND STORAGE

Personal Precautionary Measures: Avoid contact with molten material.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials. Minimize dust generation and accumulation. In the United States of America, refer to NFPA® Pamphlet No. 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries."

Storage: Keep container closed.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Country specific exposure limits have not been established or are not applicable unless listed below.

- **Ventilation:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances; such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
- **Respiratory Protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or

For other information, contact Westlake Chemical Corporation Customer Service 1-800-545-9577 (Monday-Friday, 7:30am-5:00pm - central standard time)



canister. Contact health and safety professional or manufacturer for specific information. **Eye Protection:** Wear a face shield when working with molten material. **Skin Protection:** When material is heated, wear gloves to protect against thermal burns. **Recommended Decontamination Facilities:** eye bath, washing facilities

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: solid Color: white Odor: slight Specific Gravity: 1 (25 °C) Softening Point: >100 °C Solubility in Water: negligible Flash Point: not applicable, combustible solid Thermal Decomposition Temperature: 498 °C (method unspecified)

## **10. STABILITY AND REACTIVITY**

Stability:

Incompatibility: Hazardous Polymerization: Not fully evaluated. Materials containing similar structural groups are normally stable. Material reacts with strong oxidizing agents. Will not occur.

# **11. TOXICOLOGICAL INFORMATION**

Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

Data for this material or a very similar material Oral LD-50:(rat) Dermal LD-50: (rabbit)

Skin Irritation (guinea pig) Skin Sensitization: (guinea pig) >6,400 mg/kg > 2,000 mg/kg slight none

# 12. ECOLOGICAL INFORMATION

Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

This material has not been tested for environmental effects.

# 13. DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Incinerate.

For other information, contact Westlake Chemical Corporation Customer Service 1-800-545-9577 (Monday-Friday, 7:30am-5:00pm - central standard time)



### 14. TRANSPORT INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.

DOT (USA)

Class not regulated

Sea - IMDG (International Maritime Dangerous Goods)

Class not regulated

Air - ICAO (International Civil Aviation Organization)

Class not regulated

### **15. REGULATORY INFORMATION**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS (Canada) Status: noncontrolled

SARA 313: none, unless listed below

Carcinogenicity Classification (components present at 0.1% or more): none, unless listed below

For other information, contact Westlake Chemical Corporation Customer Service 1-800-545-9577 (Monday-Friday, 7:30am-5:00pm - central standard time)



**TSCA (US Toxic Substances Control Act):** This product is listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

Inventory of Existing Chemical Substances in China: All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

#### **16. OTHER INFORMATION**

For other information, contact Westlake Chemical Corporation Customer Service 1-800-545-9577 (Monday-Friday, 7:30am-5:00pm - central standard time)

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.

Highlighted areas indicate new or changed information.

For other information, contact Westlake Chemical Corporation Customer Service 1-800-545-9577 (Monday-Friday, 7:30am-5:00pm - central standard time)