

Revision Date: 10/22/2007

MSDSUSA/ANSI/EN/150000068958/Version 2.0

0032280030/0000821294

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	P1010PL-1 Amorphous Polyolefin
Product Identification Number(s)	E3093701
Manufacturer/Supplier	Eastman Chemical Company 200 South Wilcox Drive Kingsport, TN 37660-5280 US +14232292000
MSDS Prepared by	Eastman Product Safety and Health
Chemical Name	not applicable
Synonym(s)	30937-00 984448
Molecular Formula	not applicable
Molecular Weight	not applicable
Product Use	research and development sample
OSHA Status	nonhazardous

For emergency health, safety, and environmental information, call 1-423-229-4511 or 1-423-229-2000.

For emergency transportation information, in the United States: call CHEMTREC at 800-424-9300 or call 423-229-2000.

2. COMPOSITION INFORMATION ON INGREDIENTS

(Typical composition is given, and it may vary. A certificate of analysis can be provided, if available.)

Weight % 100%

Component polymer(s) CAS Registry No. proprietary

3. HAZARDS IDENTIFICATION

CAUTION!

MOLTEN MATERIAL WILL PRODUCE THERMAL BURNS

HMIS® Hazard Ratings:

Health - 1, Flammability -1, Chemical Reactivity - 0

HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

4. FIRST-AID MEASURES

Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms persist.

Eyes: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention. If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin: Wash with soap and water. Get medical attention if symptoms occur. If burned by contact with

©COPYRIGHT 2007 BY EASTMAN CHEMICAL COMPANY

Visit our website at www.EASTMAN.com or email emnmsds@eastman.com

Page 1

MARKETED BY

HARWICK STANDARD DISTRIBUTION CORPORATION

EASTMAN MATERIAL SAFETY DATA SHEET

Revision Date: 10/22/2007

MSDSUSA/ANSI/EN/150000068958/Version 2.0

0032280030/0000821294

molten material, cool as quickly as possible. Do not peel material from skin. Get medical attention.

Ingestion: Seek medical advice. Material is not expected to be absorbed from the gastrointestinal tract so that induction of vomiting should not be necessary.

Note to Physicians: Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

5. FIRE FIGHTING MEASURES

Extinguishing Media: water spray, dry chemical, carbon dioxide

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products: carbon dioxide, carbon monoxide

Unusual Fire and Explosion Hazards: Powdered material may form explosive dust-air mixtures.

6. ACCIDENTAL RELEASE MEASURES

Sweep or scoop up and remove.

7. HANDLING AND STORAGE

Personal Precautionary Measures: Avoid contact with molten material.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials. Minimize dust generation and accumulation. In the United States of America, refer to NFPA® Pamphlet No. 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries."

Storage: Keep container closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Country specific exposure limits have not been established or are not applicable unless listed below.

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances; such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: dust

Eye Protection: It is a good industrial hygiene practice to minimize eye contact. Wear a face shield when working with molten material.

Skin Protection: It is a good industrial hygiene practice to minimize skin contact., When material is heated, wear gloves to protect against thermal burns.

Recommended Decontamination Facilities: eye bath, washing facilities



Revision Date: 10/22/2007

MSDSUSA/ANSI/EN/150000068958/Version 2.0

0032280030/0000821294

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: solid (pellet)

Color: colorless Odor: odorless

Specific Gravity: < 1 (estimated)

Melting Point: 160 °C

Solubility in Water: negligible

Flash Point: not applicable, combustible solid

Thermal Decomposition Temperature: Thermal stability not tested. Low stability hazard expected

at normal operating temperatures.

10. STABILITY AND REACTIVITY

Stability: Not fully evalu

Not fully evaluated. Materials containing similar structural groups

are normally stable.

Incompatibility:

Material reacts with strong oxidizing agents.

Hazardous Polymerization:

Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

12. ECOLOGICAL INFORMATION

Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

This material has not been tested for environmental effects.

13. DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Incinerate.

14. TRANSPORT INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



Revision Date: 10/22/2007

MSDSUSA/ANSI/EN/150000068958/Version 2.0

0032280030/0000821294

DOT (USA)

Class not regulated

Sea - IMDG (International Maritime Dangerous Goods)

Class not regulated

Air - ICAO (International Civil Aviation Organization)

Class not regulated

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS (Canada) Status: noncontrolled

SARA 313: none, unless listed below

Carcinogenicity Classification (components present at 0.1% or more): none, unless listed below

TSCA (US Toxic Substances Control Act): All components of this product are listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

16. OTHER INFORMATION

Visit our website at www.EASTMAN.com or email emnmsds@eastman.com

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.

Highlighted areas indicate new or changed information.