### MATERIAL SAFETY DATA SHEET



# **MASTERMIX INSOLUBLE SULFUR 4162 SLAB-70**

Version Number 1.8 Revision Date 08/14/2007 Page 1 of 6 Print Date 8/14/2007

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### **EXCEL POLYMERS LLC**

14330 Kinsman Road, Burton, OH 44021

Telephone : Product Stewardship (440) 834-4644

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

or accident)

Product name : MASTERMIX INSOLUBLE SULFUR 4162 SLAB-70

Product code : AD0000072960

Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Stearic acid	57-11-4	1 - 5
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	5 - 10
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	5 - 10

# 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Particulates, like other inert materials can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Particulates, like other inert materials can be mechanically irritating.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

MARKETED BY





## **MASTERMIX INSOLUBLE SULFUR 4162 SLAB-70**

Version Number 1.8 Revision Date 08/14/2007 Page 2 of 6 Print Date 8/14/2007

Medical Conditions
Aggravated by Exposure:

: None known.

#### 4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

### 5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit
Lower explosion limit
: Not applicable
: Not applicable
: Not applicable

Suitable extinguishing media : Water spray, Dry powder, Foam, Carbon dioxide (CO2).

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

impervious gioves, boots and coveraits.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section

13 of this MSDS for proper disposal methods.

## 7. HANDLING AND STORAGE

### MATERIAL SAFETY DATA SHEET



# MASTERMIX INSOLUBLE SULFUR 4162 SLAB-70

Version Number 1.8 Revision Date 08/14/2007

Page 3 of 6 Print Date 8/14/2007

Handling

Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Storage

Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.

Eye/Face Protection

Safety glasses with side-shields

Hand protection

Protective gloves

Skin and body protection

Long sleeved clothing

Additional Protective

Measures

Safety shoes

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures

Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

## Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Petroleum distillates, hydrotreated heavy naphthenic	500 ppm 2,000 mg/m3	PEL:		OSHA Z1
Petroleum distillates, solvent dewaxed heavy paraffinic	500 ppm 2,000 mg/m3	PEL:		OSHA Z1
Stearic acid	10 mg/m3	Time Weighted Average (TWA):	Total dust. as stearates	ACGIH
	10 mg/m3	Time Weighted Average (TWA):		ACGIH

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid

Evaporation rate

: Not applicable : Not determined

Appearance

: pellets, Slabs, sheets

Specific Gravity Bulk density

Color

: NO PIGMENT

: Not established

### MATERIAL SAFETY DATA SHEET



## **MASTERMIX INSOLUBLE SULFUR 4162 SLAB-70**

Version Number 1.8 Revision Date 08/14/2007

Page 4 of 6 Print Date 8/14/2007

Odour

:

: Characteristic rubber odor Vapour pressure

: Not applicable

Melting point/range Boiling Point: : Not determined: Not applicable

Vapour density pH

: Not applicable : Not applicable

Water solubility

: Insoluble

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

: Will not occur.

Conditions to avoid

Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials

: Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
57-11-4	Stearic acid	Irritant	Eyes, Skin.		
64742-52-5	Petroleum distillates, hydrotreated heavy naphthenic			hydrotreated heavy	Eyes, Skin.
64742-65-0			Eyes, Skin.		

#### LC50/LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57-11-4	Stearic acid	Oral LD50	4,600 mg/kg	rat
	Dermal LD50	> 5 gm/kg	rabbit	

### 12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

**Environmental Toxicity** 

: Chemicals are not readily available as they are bound within the

polymer matrix.





# MASTERMIX INSOLUBLE SULFUR 4162 SLAB-70

Version Number 1.8 Revision Date 08/14/2007 Page 5 of 6 Print Date 8/14/2007

Bioaccumulation Potential

Chemicals are not readily available as they are bound within the

polymer matrix.

Additional advice

: Not applicable

### 13. DISPOSAL CONSIDERATIONS

Product

: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging

Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

### 14. TRANSPORT INFORMATION

U.S. DOT Classification

Refer to specific regulation.

ICAO/IATA (air)

: Refer to specific regulation.

IMO / IMDG (maritime)

: Refer to specific regulation.

# 15. REGULATORY INFORMATION

US Regulations:

**OSHA** Status

: Classified as hazardous based on components.

TSCA Status

All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition

: Not applicable

65

SARA Title III Section 302 Extremely Hazardous Substance

#### MATERIAL SAFETY DATA SHEET



## MASTERMIX INSOLUBLE SULFUR 4162 SLAB-70

Version Number 1.8 Revision Date 08/14/2007

Page 6 of 6 Print Date 8/14/2007

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No. 57-11-4

DSL : A

All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

## 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.