



# HARWICK

## STANDARD

ISO 9001-2015 REGISTERED

## Technical Data Sheet

---

### Potassium Stearate

Potassium Stearate is suggested for use as an acid scavenger in polyolefins. This particular stearate also exhibits a high melting point, which allows its use as a high temperature processing aid in a variety of thermosets, plastics, and other elastomers. Potassium stearate can also be used as a vulcanization promoter in nitrile rubber.

The Potassium Stearate is in the form of free-flowing, fine, white powder.

#### TYPICAL PROPERTIES

Total Ash (Potassium Oxide), %	12.0
Free Fatty Acid, %	0.5
Moisture, %	0.7
Fineness through 100 Mesh, %	95

03/23/2000 Revised 10/15/2020

---

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT, OR SPECIAL DAMAGES ARISING, DIRECTLY, OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

**HARWICK STANDARD DISTRIBUTION CORPORATION**

60 S. SEIBERLING ST. • P.O. BOX 9360 • AKRON, OH 44305-0360 • U.S.A.

PHONE: (330) 798-9300 • [www.harwick.com](http://www.harwick.com)