



# HARWICK

## S T A N D A R D

ISO 9001-2015 REGISTERED

## Technical Data Sheet

---

### Stan-Lube 60P

Stan-Lube 60P is a medium to high viscosity hydrocracked paraffinic process oil that can be used in rubber compounds to aid in processing. This medium to high viscosity provides permanence at elevated temperatures and is typically used in non-polar compounds such as EPDM and EPR.

### TYPICAL PROPERTIES

Viscosity at 100 °C, cSt	12.4
Specific gravity @ 60 °F	0.8740
Volatility, Mass % @ 225 °F	0.02
Pour Point, °C	-15

08/06/2019

---

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT, OR SPECIAL DAMAGES ARISING, DIRECTLY, OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

### **HARWICK STANDARD DISTRIBUTION CORPORATION**

60 S. SEIBERLING ST. • P.O. Box 9360 • AKRON, OH 44305-0360 • U.S.A.

PHONE: (330) 798-9300 • FAX: (330) 798-0214

[www.harwick.com](http://www.harwick.com)