



WINGSTAY® 29


Mixed para oriented styrenated diphenylamines

KEY ADVANTAGES

- Highly active antioxidant
- Low volatility
- Low staining characteristics
- Does not activate scorch nor cause bin cure

APPLICATIONS

- Provides resistance to heat and flex fatigue in rubber applications such as belts and industrial rubber goods Very effective in polychloroprene
- Stabilization of synthetic polymers, lattices and lubricants
- Protection of medium and high voltage polyethylene cables
- Protection of adhesives



TYPICAL PROPERTIES

Physical Form	Clear viscous liquid (Wingstay 29 Powder is available as 70% active on inert silica)
Specific Gravity	1.080
Average molecular weight	390
Gardner color	5
Viscosity @ 25 °C (mPa.s)	35,000
Refractive index @ 25 °C	1.639
Para-substitution, mole %	75
Bound styrene/diphenylamine molar ratio	2.1
Solubility	Soluble in aromatics, Ketones, and alcohols, insoluble in water
Food Contact	Compliance information available upon request

PACKAGING, HANDLING AND STORAGE

- Packaging: Wingstay 29 Liquid: Open head metal drum with two sealable bungs. (2 in. and 3/4 in.). Dimensions (mm): Diameter: 610, H: 915. Net weight: 210 kg (463 lbs). Wingstay 29 Powder, 70% active: 24 x 25 kg cardboard boxes stretch wrapped on a pallet. Dimensions (mm): L: 1220, W: 820, H: 1260. Net weight: 567 kg (1250 lbs).
- Storage: Store in dry, well ventilated area away from direct sources of heat or sun.
- Please read the material safety data sheet (MSDS) prior to use. Copy can be obtained on www.quickfds.com.

NOTE: Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product(s) is/are appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, or whether such use will infringe the intellectual property rights of third parties.

www.omnova.com



Americas

World Headquarters 175 Ghent Road Fairlawn, OH 44333 USA

PHONE +1 330 869-4323 FAX +1 330 869-4338

customer service +1 888 253-5454

EMAIL pccustserv@omnova.com

Europe / Middle East / Africa / India

14, avenue des Tropiques Z.A. de Courtaboeuf 2 - Villejust 91955 Courtaboeuf Cedex France

PHONE +33 (0) 1 69 29 27 00

FAX +33 (0) 1 69 29 27 01

Asia

Unit 09-11, 7th Floor, Greenland Riverside International Center 596 Long Hua Middle Road, Xu Hui District Shanghai. 200032. China

PHONE +86 (21) 6473 2525 FAX +86 (21) 5421 1766

ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM

All trademarks - OMNOVA Solutions

© 2012 OMNOVA Solutions; March 2012